

DID VIDEO WALL HDMI SPLITTER

HDMI Splitter Describe



HDMI series of professional distributor uses high performance video processing chip, input and output are using standard Type-A HDMI lock head; transmission can play a role assignment, with up to 1.65Gbps bandwidth, single channel bandwidth is 3.0Gbps compatible with 480p support, 720p, 1080i, 1080p and 1920x1200 resolution, HDMI is the role of a distributor the way the computer without signal attenuation distribution to a plurality of display devices, the factory standard products from 1TO4 to 1TO32; other non standard products can call custom processing, is used in the field of military,

multimedia teaching, video conference, finance, scientific research, meteorology and other fields.

HDMI Splitter Model

Product type	Model	SIZE (mm)
HDMI 1*4	HK-DID-VS-HDMI-1I-4	203mm×120mm×50mm
HDMI 1*8	HK-DID-VS-HDMI-1-8	1U, 430mm×250mm×44mm
HDMI 1*16	HK-DID-VS-HDMI-1-16	1U, 430mm×250mm×44mm

VGA Splitter Characteristic

The HDMI Splitter supports the international standard HDCP content protection version 1.2; support HDMI1.3 version, fully compatible with HDCP, support video format color: color depth of 24 bit /36 bit color depth; HDMI distributor support audio formats: LPCM, DOLBY-AC3, DTS7.1, DSD; using high bandwidth chip, high performance image processing and long distance signal transmission distortion gain compensation; the whole patch SMD process, ESD electrostatic protection technology characteristic of the frame type conductive chassis, effectively shield the interference signal for bad installation environment.

HDMI Splitter parameter

Support video format:

VGA: 640×480 to 1920×1200

HDTV/DTV: 1080P/1080I/720P/576P/576I/480P/480I

Date transmission rate: 2.25Gbps×3

Temperature : -15 to +55℃

Humidity: 5 to 90%RH

Output : DC 5V

Power format: AC100V~240V(50Hz/60Hz)

Chassis panel: oxidizing wire

Warranty : one year

Marking: manual, power line, warranty card, certificate of qualification.